

In compliance with Regulation 305/2011/EU of the European Parliament and of the Council of 9 March 2011 (the Construction Products Regulation - CPR) this certificate applies to the construction product

Mosser Brettsperrholz; Mosser Cross-Laminated Timber; Mosser X-Lam; Mosser CLT

according to the product specification listed in the current addendum to this certificate placed on the market by

Company MOSSER LEIMHOLZ GMBH Fohlenhof 2 AT-3263 Randegg

and produced in the manufacturing plant

AT-3263 Randegg, Perwarth 88

This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in

ETA-23/0498, issued on 22.08.2023

and

EAD 130005-00-0304

under system 1 for the performance set out in the ETA are applied and that the factory production control conducted by the manufacturer is assessed to ensure the constancy of performance of the construction product.

CERTIFICATE OF CONSTANCY OF PERFORMANCE

Certificate number: 1359-CPR-0855 Date of first issue: 24.08.2023 Date of issuance: 24.08.2023

This certificate will remain valid as long as neither the ETA, the EAD, the construction product, the AVCP methods nor the manufacturing conditions in the plant are modified significantly, unless suspended or withdrawn by the notified product certification body.

For the validity of this certificate see www.holzforschung.at.

Dr. Andreas Neumüller

Authorised signatory

Dr. Manfred Brandstätter Head of the Certification Body





Addendum to certificate 1359-CPR-0855

Date of issuance: 24.08.2023

Scope of certification for the following products:

Mosser Brettsperrholz; Mosser Cross-Laminated Timber; Mosser X-Lam; Mosser CLT

Solid wood slabs to be used as structural elements in building

Structure:

minimum 3-layers, layers arranged perpendicular

(angle of 90°), maximum 7 layers, symmetrical construction

Strength classes of the laminations:

C 24

Thickness:

60 - 280 mm

Width × length:

max. 1,25 × 14,0 m

Service classes:

1, 2

Wood species:

PCAB - spruce/ ABAL - fir;

Adhesive:

- Finger joints

Type I: MUF according to EN 301

- Surface bonding:

Type I: PUR according to EN 15425